

# Installation Instructions

DarPro Fry Oil Filter Machine

# SUPERSORB<sup>®</sup> CARBONPADS

## Getting the most out of your frying program

- 1)** First, please remove the DarPro support screen and hold down bar from the filter tank.



- 2)** Second, install the Filtercorp F-16 Unifit Adapter Kit inside the filter tank with carbon pad (rough side facing down) into the filter tank. See Picture 1. Then connect Filtercorp Unifit flex hose's quick disconnect part to the DarPro pick up hose's female quick disconnect. (The filter tank hose will not be used.) See picture 2. Place DarPro crumb basket in front of the filter tank as normal. The read tank cover will not be used with this conversion. See Picture 3.

**Picture 1**



**Picture 2**



**Picture 3**



DarPro Filter Machine is now ready to filter oil (must be at least 300°F temperature). The Filtercorp SuperSorb<sup>®</sup> CarbonPad must be used daily. No powder additives are needed with the Filtercorp's CarbonPad. Simply dispose and replace a new CarbonPad every day. Wash Filtercorp Unifit Adapter with hot water and set to dry completely.

- 3)** After filtering all fryers, carefully scrape the crumb debris off the CarbonPad using a spatula or putty knife. The CarbonPad is now ready to filter fryers for the day's 2nd filtration. Always use a new CarbonPad every day.



## **FILTERCORP**

9805 NE 116th Street  
PMB A-200  
Kirkland, WA 98034  
USA

Toll Free: (800) 473-4526  
Telephone: (425) 820-4850  
Fax: (425) 820-2816  
Web: [www.filtercorp.com](http://www.filtercorp.com)



[www.filtercorp.com](http://www.filtercorp.com)